



- Softly sculpted surface pattern on both sides
- Designed to hang from ceilings in large, open rooms
- Excellent sound absorption across all frequencies
- Baffle size of 24" x 48" by 3" thickness

SONEX[®] One Baffles

Product Information

SONEX One Baffles are an ideal solution to reverberation and overall noise problems. These versatile baffles can be used in a variety of settings including: auditoriums, gymnasiums, indoor swimming pools, recreation centers and production facilities. SONEX One Baffles are made from pinta's exclusive willtec[®] foam, which is Class 1 fire-rated according to ASTM E 84 for flame spread and smoke density. willtec natural also meets the corner burn test UL 1715.

In addition to its high fire safety rating, willtec foam provides excellent sound absorption across all frequencies and helps prevent noise buildup that interferes with speech intelligibility.


SONEX One Baffles are available in natural or water-based HPC-coated finishes. Our exclusive HPC formulation protects the foam from dust and dirt and makes it possible to wipe baffles clean using only a damp cloth.

SONEX One Baffles are equipped with integrated straps and grommets for easy installation on ceiling-mounted cables or chains. Baffles can be aligned in the same direction or arranged so that every other baffle is turned 90 degrees. For detailed installation instructions, please see our baffle installation guide.

California State University – Dominguez Hills



willtec meets ASTM E 84 Class 1 fire rating



SONEX® One baffles in music room



Applications

- Multipurpose rooms and gymnasiums
- Large classrooms or music rooms
- Manufacturing facilities
- Aquatic centers and indoor pools
- Any large, open room with reverberation problems

Physical Data—willtec® foam

Material	Open-cell melamine-based foam
Density	0.5 to 0.7 lbs./cubic ft. (ASTM D3574-77)
Long-Term Service Temperature	302° F
Fire Resistance	Class 1 per ASTM E 84 (all finishes) Meets UL 1715 (willtec natural)
Flame Spread per ASTM E 84	Natural: 5 HPC-coated: 15
Smoke Density per ASTM E 84	Natural: 50 HPC-coated: 100
Microbial Growth	Passes UL 181, section 11
Fungus Resistance	Rating 0 per ASTM G21
Finishes	Natural (white and light grey) or HPC-coated (standard, premium and custom colors)

Sound Absorption

Finish	Thickness	Sabins per Baffle per ASTM C423-90a						Average
		125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	
Natural (white and light grey)	3"	2.3	5.7	10.5	15.3	18.6	24.8	12.9
HPC-coated (standard, premium and custom colors)	3"	.076	3.96	10.92	18.2	18.45	18.05	12.9

Other Products

pinta acoustic, inc. manufactures a broad range of acoustical materials including:

- CONTOUR® Ceiling Tiles
- HARMONI Ceiling Tiles
- WHITELINE® Ceiling Tiles
- SQUARELINE® Metal Ceiling Tiles
- SONEX® Baffles and Panels
- SONEX Clean Baffles, Panels and Ceiling Tiles
- PHONSTOP™ Ceiling and Wall Tiles
- WHISPERWAVE™ Panels, Baffles, Ceiling Clouds and Awnings
- PROSPEC® Barriers, Foams and Composites