

WHITELINE® Ceiling Panels Product Information



WHITELINE® suspended, lay-in grid ceiling panels offer extraordinary acoustic value for everyday interior environments, such as classrooms, open-plan offices and retail spaces. Economically priced, these ceiling tiles are ideal for projects where the primary concerns are overall budget and lasting, quality products. WHITELINE panels feature superior sound-absorptive, open-cell, non-fibrous WILLTEC® foam cores laminated with smooth, white fleece on one side and black fleece on the opposing surface. Custom panel sizes, thicknesses, colors and printing are available.

>> | Advantages

- Simple, quick and easy to install
- Panels can be exposed to view on one or the other side
- Fits within 9/16" or 15/16" (14 mm or 24 mm) typical suspension grid
- Lightweight, open-cell, non-fibrous, lay-in panels
- Provides outstanding sound absorption

2601 49th Avenue North, Suite 400
Minneapolis, MN 55430
+1 (612) 355-4200
1-800-662-0032
sales@pinta-acoustic.com
www.pinta-acoustic.com

Applications

- Educational facilities, classrooms, libraries and lecture halls
- Corporate, open-plan and private offices
- Retail department, supermarket and boutique stores
- Medical clinics, hospitals, pharmacies and assisted-living facilities
- Municipal public works, police precincts and firehouses
- Government courthouses and post offices
- Transport, airport, railway and bus terminals
- Restaurants, theaters and concert venues

Material

- Class A fire rated to ASTM E84
- Lightweight, open-cell, non-fibrous WILLTEC® expanded melamine foam core panels laminated with smooth white or black translucent fleece on opposing sides
- Panels can be exposed to view on one side or the other, or mixed for a checkerboard pattern
- High light reflectance value of 0.89, white fleece side
- Custom colors and printing options are available

Size

- Offered in a variety of standard sizes: 2' x 2', 4', 6' and 8'; (610 x 610, 1219, 1829 and 2438 mm) 4' x 4' and 4' x 8' (1219 x 1219 and 1219 x 2438 mm) and custom
- Typical panel thickness: 9/16" (14 mm); WILLTEC panel cores can be produced thicker to increase sound absorption according to specific project NRC requirements

Installation

- WHITELINE® square-edge, suspended, lay-in grid ceiling panels are simple, quick and easy to install in any standard 9/16" or 15/16" (14 mm or 24 mm) exposed grid
- Easy to handle with soft white cotton gloves and to produce any cut-to-fit panel sizes on-site
- Non-fibrous WILLTEC expanded melamine foam core panels produce little to no dust during installation compared to mineral fiber-, rock wool- and fiberglass-based products



Physical Data—WILLTEC® foam

Tensile Strength	8 PSI (ASTM D3574-77)
Density	0.7 lbs./cu. ft. (0.3 Kg/cu. m)
Elongation	8% (ASTM D3574-77)
Heat Conductivity	K factor = 0.24 at 50°F (10°C)
Long-Term Service Temperature	302°F (150°C)
Fire Resistance	Class 1 (ASTM E84) CAN ULCS-102
Flame Spread per ASTM	E84 0 CAN ULCS-102
Smoke Density per ASTM	E84 65
Color	White/Black

Sound Absorption

Test ASTM C423-90a; Mounting Type E

Frequency (Hz)	Thickness 0.6" (15 mm)
125	0.27
250	0.60
500	0.64
1000	0.80
2000	0.91
4000	1.02
NRC	0.75

>> Other Products

- Ceiling Tiles
- Ceiling Clouds
- Wall Panels
- Baffles
- Barriers, Foam and Composites

2601 49th Avenue North, Suite 400
 Minneapolis, MN 55430
 +1 (612) 355-4200
 1-800-662-0032
 sales@pinta-acoustic.com
 www.pinta-acoustic.com